




PRODUCT INFORMATION

TF Touch

HYPERSTATION





FEATURES

- **Deep UI customization:** It can be flexibly customized according to different application scenarios.
- **Supports TCP, UDP, WebSocket, OSC, ModBus, RTSP, and data types like UTF-8, GBK, Hex, Int, Float, Double.**
Converts TCP/UDP data to RS-232/RS-485 via serial servers for extended use, supporting diverse devices and applications.
- **Built-in logic editing function,** supports cloud data feedback and real-time control.
- **Monitoring & Maintenance:** Supports status feedback for audio, lighting, visuals, smart power, and networks, showing real-time device status, switch port connections, and network speeds.
- **Network publishing:** Supports remote publishing of projects from editing terminal to control terminal for download and use
- **.Timed Delay:** Set delayed or scheduled tasks to auto-switch scene modes for smarter control.
- **Visualization:** Supports capturing camera feeds via RTSP protocol, controlling camera movement direction, speed and focus adjustment, enabling real-time video monitoring and management.

Model: Hyperstation

Capacitive Touch:	21.5-inch*2	Language:	Chinese/English
Communication:	Wired Network (LAN1)	Resolution:	1920*1080
RS232*2:	RS485*2	Power Supply:	AC 220V, 1U Rack Power Supply
Network Protocols:	TCP, UDP, WebSocket, OSC, ModBus and RTSP	Version:	RK3588 4+64G/RK3588 8+128G/ RK3566 4+64G
Data Types:	UTF-8, GBK, Hex, Int, Float, Double	Dimensions:	588*700*314 ∠40°